



Larrondo LOIU (VIZCAYA) España  
P.O. Box 1.323/48086 Bilbao  
Tel. 34-(4) 4 71 13 00  
Fax. 34-(4) 4 53 16 36

Management Systems  
Certified by  
LRQA  
ISO 9001 / SGI 6000360  
ISO 14001 / SGI 1970678

**FLOW TECHNOLOGY LTD**  
**TEST CERTIFICATE**  
**VERIFIED TRUE**  
**COPY OF ORIGINAL**

ACEROS INOXIDABLES  
**OLARRA**

**OLARRA U.K. LTD.**  
**FOREST PARK - CLEOBURY MORTIMER**  
**NR KIDDERMINSTER - DY 14 9BD - ENGLAND**

Trade Mark - Zeichen des Lieferwerkes  
Anagrama del suministrador   
Works Inspector Stamp - Werkssachverständiger  
Sello del Inspector 

|  |                                 |   |  |  |                                    |  |        |                          |  |   |      |
|--|---------------------------------|---|--|--|------------------------------------|--|--------|--------------------------|--|---|------|
| Certificate type - APZ Nach<br>Certificado tipo <b>EN 10204/3.1</b>  |                                 | Certificate n° - Prüf-Nr<br>Certificado n° <b>296951</b>                                      |  | Date - Datum - Fecha<br><b>23 - 12 - 2016</b>                            |                                    |  |        |                          |  |   |      |
| Our order N°<br>Werks - Nr <b>617568</b><br>N° de Referencia   |                                 | Heat<br>Schmelze <b>424796</b><br>Colada  |  | Your order N°<br>Bestell - Nr <b>0L7534</b><br>Pedido N°                 |                                    |  |        |                          |  |   |      |
| Steel Grade<br>Werkstoff <b>316-S-11 AV</b><br>Calidad   |                                 |   | According to<br>Entsprechend <b>BS 970:PART 3:1991.</b><br>Corresponde   |  |                                    |  |        |                          |  |   |      |
| Shape and Size - Gegenstad<br>Perfil y dimensión<br><b>HEXAGON 27,94 mm</b>  |                                 | Tolerance - Toleranz<br>Tolerancia<br><b>h 11 /DIN 176</b>                                    |  | Bundles<br>Bunde <b>4</b><br>Bultos                                      | Bars<br>Stäbe <b>152</b><br>Barras |  |        |                          |  |   |      |
|  |                                 |   |  | Weight<br>Gewicht <b>2586 Kg</b><br>Peso                                 |                                    |  |        |                          |  |   |      |
| Requirements - Anforderungen - Exigencias  |                                 |   |  |  |                                    |  |        |                          |  |   |      |
| EN 10.088-3.2014.<br>EN 10.272-2007.<br>ASTM A 182/A 182M-16.<br>ASTM A 479 / A 479M-15.<br>ASTM A 276/A 276M-16a.<br>ASME SA 479 / SA 479M-15<br>SAE AMS 5653H-12.<br>NACE MR-0175/ISO 15156-3 2015.<br>NACE MR-0103-12/ISO 17945-2015.<br>316S31AV-1.4404-1.4401-Type 316-Type 316L. |                                 |   | PED 2014/68/EU, Annex I, Parag.4.3/DGR 2014/68/EU<br>Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC |  |                                    |  |        |                          |  |   |      |
| Melting process / Erschmelzungsart / Proceso de Fusión<br><b>E.A.F. / A.O.D.</b>   |                                 |   | Heat treatment / Wärmebehandlung / Tratamiento térmico<br><b>1060C 4H/Std WATER/WASSER/AGUA</b>                  |  |                                    |  |        |                          |  |   |      |
| <b>Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estrado-</b>  |                                 |   |  |  |                                    |  |        |                          |  |   |      |
| Test results - Ergebnis der Prüfungen - Resultados de los ensayos  |                                 |   |  |  |                                    |  |        |                          |  |   |      |
| Dimension of Specimen<br>Abmessungen des Probestabes<br>Medida de las probetas   |                                 | Rp0.2%<br>N/mm2<br>MPA  | Rp 1%<br>N/mm2<br>MPA  | Rm<br>N/mm2<br>MPA   | A<br>%L 5D                         | A<br>%L 4D                                 | Z<br>% | Hardness<br>Härte<br>HBw | Impact test / Kerschlag / Resiliencia<br>ISO V Jules |   |      |
| RD. 10,00 mm.  |                                 | Min. 325  | 375  | 550  | 20                                 |  |        |                          |  |   |      |
|  |                                 | Max.  |  |  |                                    |  |        |                          |  |   |      |
| Temperature °C<br>20   | Spec. N°<br>Probe Nr.<br>Pro N° | 1   | 428  | 520  | 640                                | 40   | 43     | 72                       | 197  |   |      |
|  | C                               | Si  | Mn   | P  | S                                  | Cr   | Mo     | Ni                       | Cu   | N   | Co   |
| Min.   |                                 |   |  |  |                                    | 16,50                                      | 2,00   | 11,00                    |  |   |      |
| Max.   | 0,030                           | 1,00  | 2,00   | 0,045  | 0,030                              | 18,50                                      | 2,50   | 14,00                    | 0,70   |   |      |
|  | 0,018                           | 0,48  | 1,54   | 0,039  | 0,027                              | 17,10                                      | 2,01   | 11,05                    | 0,42   | 0,0255  | 0,21 |
| Visual and dimensional inspection<br>Besichtigung und Ausmessung<br>Control visual y dimensional <b>O.K.</b>   |                                 | Radioactivity inspection<br>Radioaktivitätskontrolle<br>Control de Radioactividad <b>O.K.</b> |  | Antimixing test<br>Spektroskop Verwechslungspr<br>Antimezcla <b>O.K.</b> |                                    | Grain Size<br>Korngröße<br>Tamaño de grano |        |                          |  |   |      |
| Remarks - Bemerkungen - Observaciones  |                                 |   |  |  |                                    |  |        |                          |  | EDV / EDP<br>Acc. EN 10.204<br>Marian Tejedo<br>Quality Mng.<br><br>Works Inspector<br>Der Werkssachverständige<br>Inspector de fábrica |      |
| IC test acc./IK prüfung nach ASTM A 262 E.15. OK<br>Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK<br><br>F12746<br>1/2" BSPP C/S X 3/8" NPT M/M RED ADAPTOR 10K 316L   |                                 |   |  |  |                                    |  |        |                          |  |   |      |