Larrondo LOTU (VIZCAYA) España P.O. Box 1.323/48080 Bilbao Tel. 34-(4) 4 71 13 00 Fax.34-(4) 4 53 16 36

Management Systems Certified by LRQA ISO 9001 / SGI 6000360 ISO 14001 / SGI 1870678

ACEROS INOXIDABLES



Trade Mark - Zeichen des Lieferwerkes Anagrama del suministrador

Works Inspector Stamp - Werkssachverständiger Sello del Inspector

OLARRA U.K. LTD. FOREST PARK - CLEOBURY MORTIMER NR KIDDERMINSTER - DY 14 9BD - ENGLAND

Certificate type - APZ Nach EN 10204/3.1										Certificate n° - Prüf-Nr Certificado n° 285366					Date - Datum - Fecha 20 - 09 - 2016		
Our order N° Heat Werks - Nr 606532 Schmelze 41 N° de Referencia Colada						e 41 [°]	7691		Your order N° Bestell - Nr OL7352 Pedido N°								
Steel Grade Werkstoff 316-S-11 AV Calidad										a AWA AMARA	According Entsprect Correspo	hend BS	970:PA	RT 3:1	1991.		
Shape and Size - Gegenstad Perfil y dimensión HEXAGON 31,75 mm							Tolerand Tol h 11 /	eranci	a		Bundles Bunde Bultos	Bars Stäbe Barras		Weight Gewitcht Peso	3837 Kg		
						·	Requ	irement	s - Aní	forderung	gen - Exig	encias					
EN AS AS AS NA SAI 316 PEI	TM A 47 TM A 27 ME SA 4 CE MR-(E AMS 5 S31AV- D 2014/6	2007. 2 / A 182 9 / A 479	M-15.479M- 1515 .4401 nnex I	-15 56-3 -Typ , Pa sart /	oe 316- rag.4.3 Proceso	/DGR 2 de Fusió	2014 5n			Heat!	treatment 060C 4F	/ Wärmebeha I/Std WAT	andlung / T ER/WAS	ratamient	o térmico	8/2008/MUC	
				S	olution	inneale	d/Abg	eschrec	kt/Hip	ertempl	e-Cold dr	awn/Gezoge	n/Estirado)-			
					Te	st results	s - Ero	ebnis de	er Prül	fungen -	Resultado	s de los ensa	avos				
Dimension of Specimen Abmessurgen des Probestabes Medida de las probetas			N/r	0,2%	Rp 1% N/mm2 MPA	Rm N/mm2 MPA		A %L 5D	Α	Z	Hardness Härte HBw		act test / Kersbschlag / Çesiliencia ISO V Jules				
RD. 10,00 mm.			Min.	325 3		375	550		20								
			Max.														
Temperature ℃ 20		Spec. Nº. Probe Nr. Pro Nº.	1	1 39		480	5	84	46	49	74	183					
												T -		Γ _			
	С	Si Mn P			<u>S</u>	Cr	_ -	Mo	Ni 11,00	Cu	N	Co	_				
Min,								16,50	,	2,00	11,00						

Remarks - Bemerkungen - Observaciones

18.50

17,10

2,50

2,00

0,030

Radioactivity inspection Radioaktivitätskontrolle O.K. Control de Radioactividad

0,020 🚽

IC test acc./IK prüfung nach ASTM A 262 E.14. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK

2,00

1,75

0.045

0,034

Max.

0,030

0,025

1.00

0,38

Visual and dimensional inspection Besichtingung und Ausmessung O.K. Control visual y dimensional

FLOW TECHNOLOGY LTD
TEST CERTIFICATE
VERIFIED TRUE
COPY OF ORIGINAL

0,70

0,30

0.0265

Grain Size Korngrösse Tamaño de grano

0,18

14,00

11,05

Antimixing test Spektrosk Verwechslungspr **O.K.** Antimezcla

> EDV / EDP Acc. EN 10.204 Marian Tejedo Quality Mng.

F11789
1/2" BSPP Cone Seat x 9/16" JIC Male x Male Adaptor 15K

Works Inspector Der Werkssachverständige Inspector de fäbrica