


Larrondo LOIU (VIZCAYA) España
P.O. Box 1 323/48080 Bilbao
Tel. 34-(4) 4 71 13 00
Fax.34-(4) 4 53 16 36




ACEROS INOXIDABLES


OLARRA

OLARRA U.K. LTD.
FOREST PARK - CLEOBURY MORTIMER
NR KIDDERMINSTER - DY14 9BD - ENGLAND

Trade Mark - Zeichen des Lieferwerkes
Anagrama del suministrador



Works Inspector Stamp - Werkssachverständiger
Sello del Inspector



Certificate type - APZ Nach Certificado tipo			EN 10204/3.1			Certificate n° - Prüf-Nr Certificado n°			229307			Date - Datum - Fecha 20 - 04 - 2015															
Our order N° Werks - Nr N° de Referencia			557512			Heat Schmelze Colada			390260			Your order N° Bestell - Nr Pedido N°			OL6598												
Steel Grade Werkstoff Calidad						316-S-11 AV						According to Entsprechend Corresponde						BS 970:PART 3:1991.									
Shape and Size - Gegenstad Perfil y dimensión HEXAGON 23,37 mm				Tolerance - Toleranz Tolerancia h 11 / DIN 176				Bundles Bunde Bultos		2		Bars Stäbe Barras		80		Weight Gewicht Peso		917 Kg									
Requirements - Anforderungen - Exigencias												Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC															
EN 10.088-3.2005. EN 10.272-2007. ASTM A 182 / A 182M-14a. ASTM A 479 / A 479M-14. ASTM A 276-13a. ASME SA 479 / SA 479M-13 SAE AMS 5653H-12. NACE MR-0175-2003/ISO 15156-3 2009. 316S31AV-1.4404-1.4401-Type 316-Type 316L. PED 97/23/EC, Annex I, Parag.4.3/DGR 97/23/EG																											
Melting process / Erschmelzungsart / Proceso de Fusión						E.A.F. / A.O.D.						Heat treatment / Wärmebehandlung / Tratamiento térmico						1060C 4H/Std WATER/WASSER/AGUA									
Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estirado-																											
Test results - Ergebnis der Prüfungen - Resultados de los ensayos																											
Dimension of Specimen Abmessungen des Probestabes Medida de las probetas		Rp0,2% N/mm2 MPA		Rp 1% N/mm2 MPA		Rm N/mm2 MPA		A %L 5D		A %L 4D		Z %		Hardness Härte HBw		Impact test / Kerschlag / Resiliencia ISO V Jules											
RD. 10,00 mm.		Min. 325		375		550		20																			
		Max.																									
Temperature °C 20		Spec. N° Probe Nr. Pro N°		1		423		516		638		41		44		72		197									
C		Si		Mn		P		S		Cr		Mo		Ni		Cu		N		Co							
Min.										16,50		2,00		11,00													
Max.		0,030		1,00		2,00		0,045		0,030		18,50		2,50		14,00		0,70									
		0,021		0,41		1,79		0,034		0,028		17,05		2,02		11,00		0,57		0,0260 0,20							
Visual and dimensional inspection Besichtigung und Ausmessung Control visual y dimensional				O.K.				Radioactivity inspection Radioaktivitätskontrolle Control de Radioactividad				O.K.				Anti mixing test Spektroskop Verwechslungspr Antimezcla				O.K.				Grain Size Korngröße Tamaño de grano			
Remarks - Bemerkungen - Observaciones														EDV / EDP Acc. EN 10.204 Alfredo Molina Certification Mng.													
IC test acc./IK prüfung nach ASTM A 262 E.13. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK														Works Inspector Der Werkssachverständige Inspector de fábrica													
F11907 1/4" BSPP Cone Seat x1/2" NPT Male x Male Adaptor 30K																											