

Larrondo LOIU (VIZCAYA) España
P.O. Box 1.323/48080 Bilbao
Tel. 34-(4) 4 71 13 00
Fax.34-(4) 4 53 16 36

Management Systems
Certified by
LRQA
ISO 9001 / SGI 6000360
ISO 14001 / SGI 1870678

ACEROS INOXIDABLES

OLARRA

OLARRA U.K. LTD.
FOREST PARK - CLEOBURY MORTIMER
NR KIDDERMINSTER - DY 14 9BD - ENGLAND

Trade Mark - Zeichen des Lieferwerkes
Anagrama del suministrador



Works Inspector Stamp - Werkssachverständiger
Sello del Inspector



Certificate type - APZ Nach Certificado tipo		EN 10204/3.1		Certificate n° - Prüf-Nr Certificado n°		294317		Date - Datum - Fecha 02 - 12 - 2016															
Our order N° Werks - Nr N° de Referencia		620698		Heat Schmelze Colada		422519		Your order N° Bestell - Nr Pedido N°				OL7591											
Steel Grade Werkstoff Calidad				316-S-11 AV				According to Entsprechend Corresponde				BS 970:PART 3:1991.											
Shape and Size - Gegenstad Perfil y dimensión HEXAGON 19,05 mm			Tolerance - Toleranz Tolerancia h 11 /DIN 176			Bundles Bunde Bultos		4		Bars Stäbe Barras		340		Weight Gewicht Peso		2652 Kg							
Requirements - Anforderungen - Exigencias												PED 2014/68/EU, Annex I, Parag.4.3/DGR 2014/68/EU Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC											
EN 10.088-3.2014. EN 10.272-2007. ASTM A 182 / A 182M-15. ASTM A 479 / A 479M-15. ASTM A 276-16a. ASME SA 479 / SA 479M-15 SAE AMS 5653H-12. NACE MR-0175/ISO 15156-3 2009. NACE MR-0103-12/ISO 17945-2015. 316S31AV-1.4404-1.4401-Type 316-Type 316L.																							
Melting process / Erschmelzungsart / Proceso de Fusión						Heat treatment / Wärmebehandlung / Tratamiento térmico						1060C 4H/Std WATER/WASSER/AGUA											
E.A.F. / A.O.D.																							
Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estirado-																							
Test results - Ergebnis der Prüfungen - Resultados de los ensayos																							
Dimension of Specimen Abmessungen des Probestabes Medida de las probetas		Rp0,2% N/mm2 MPA		Rp 1% N/mm2 MPA		Rm N/mm2 MPA		A %L 5D		A %L 4D		Z %		Hardness Härte HBw		Impact test / Kersbschlag / Resiliencia ISO V Jules							
RD. 10,00 mm.		Min.		325		375		550		20													
		Max.																					
Temperature °C 20		Spec. N°. Probe Nr. Pro N°.		1		459		560		642		36		39		74		207					
		C		Si		Mn		P		S		Cr		Mo		Ni		Cu		N		Co	
Min.												16,50		2,00		11,00							
Max.		0,030		1,00		2,00		0,045		0,030		18,50		2,50		14,00		0,70					
		0,020		0,66		1,54		0,033		0,028		17,05		2,01		11,00		0,33		0,0305		0,16	
Visual and dimensional inspection Besichtigung und Ausmessung Control visual y dimensional				Radioactivity inspection Radioaktivitätskontrolle Control de Radioactividad				Antimixing test Spektrosk Verwechslungspr Antimezcla				Grain Size Korngröße Tamaño de grano											
O.K.				O.K.				O.K.															
Remarks - Bemerkungen - Observaciones																							
IC test acc./IK prüfung nach ASTM A 262 E. 15. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK												FLOW TECHNOLOGY LTD TEST CERTIFICATE VERIFIED TRUE COPY OF ORIGINAL				EDV / EDP Acc. EN 10.204 Marian Tejedo Quality Mng.							
F12181 1/4" BSPP C/S X 1/8" NPT M/M ADAPTOR 10K 316L												Works Inspector Der Werkssachverständige Inspector de fábrica				363102 - 363103							