Larrondo LOIU (VIZCAYA) España P.O. Box 1.323/48080 Bilbao Tel. 34-(4) 4 71 13 00 Fax.34-(4) 4 53 16 36

Hanagement Systems Certified by LRQA ISO 9001 / SGI 6000360 ISO 14001 / SGI 1870678

ACEROS INOXIDABLES



Trade Mark - Zeichen des Lieferwerkes Anagrama del suministrador

Works Inspector Stamp - Werkssachverständiger Sello del Inspector

OLARRA U.K. LTD. FOREST PARK - CLEOBURY MORTIMER NR KIDDERMINSTER - DY 149BD - ENGLAND

Certificate type - APZ Nach EN 10204/3.1									Certificate nº - Prüf-Nr Certificado nº 265986 Date-Datum-Fechs 14 - 03 - 2016						
Wer	order Nº ks - Nr Referenc	5963 Sa	388	S	leat Schmeize Solada	407	486	Your order N° Bestell - Nr OL7136 Pedido N°							
	l Grade kstoff fad	316-S	-11 A'	V						According to Entsprechend BS 970:PART 3:1991. Corresponde					
Shape and Size - Gegenstad Perfil y dimensión HEXAGON 19,05 mm							. 1	Folerar				Bars 4 Ståbe Barra	~~~	Weight Gewitcht Peso	2578 Kg
	nex/	AGON 1	9,00	mm		h 11 /DIN 176				·		Datia	3 ·	1 630	
							Requireme	ents - A		gen - Exige					0100000001116
		3.2014.					•		Ann	ang I Ab	satz 4.3 C	ertificate	e/Zertifik	at Nr. 34	8/2008/MUC
	10.272-													•	
		32 / A 182													
		'9 / A 479	JIVI-15.												
	M A 27		47014	40											
		479 / SA		13											
		5653H-12			200										
		0175/ISC					i Ai								
		1.4404-1			-	-			**						
		EC, Ann							1						
Melti	ng proce	ss / Erschm E.A.F	•			e Fusio	n				/ Wärmebeh I/Std WAT	•			
				So	lution an	nealed	/Abgesch	reckt/l-	lipertemp	le-Cold dr	awn/Gezoge	n/Estirad	D-		
					Test	results	- Ergebnis	der P	rüfungen -	Resultado	s de los ens	ayos			
					m2 N/	o 1% mm2 IPA	m2 N/mm2		A D %L 4E	Z %	Hardness Härte HBw	Impact test / Kersbschlag / Resiliencia ISO V Jules			
RD. 10,00 mm. Min. 325					5 :	375 550		20	1						
Max.											· · · · · · · · · · · · · · · · · · ·				
	erature°C 20	Spec. No. Probe Nr. Pro No.	1	45	i2	627		40	43	73	207			***************************************	
								i	2						
7	С	Si	N	n	P			or T	Мо	Ni	Cu	N	Со		
Min.		+ -:	-	-				.50	2,00	11,00	1		—	1	
Max	0,030	1,00	2,	00	0,045	0,0		,50	2,50	14,00	0,70				
-	0,022	0,45	1.	72	0,034	0,0	29 17	,05	2,00	11,10	0,32	0,0240	0,26	1	
Besic	l and dime	ensionalins und Ausme y dimension	essung	O.K.	Radioal	tivitāts	spection kontrolle (actividad).K.	Antimixing Spektrosk\ Antimezcl	/erwechslur	ngspr O.K.	Grain Siz Komgrōs Tamaño	se		

Remarks - Bemerkungen - Observaciones

IC test acc./IK prüfung nach ASTM A 262 E.13. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK

F13565 3/8" MEDIUM PRESSURE MALE X 1/4" BSPP MALE ADAPTOR 20K 316L EDV / EDP Acc. EN 10.204 Marian Tejedo Quality Mng.

Works Inspector

Der Werkssachverständige
Inspector de fäbrica