

Larrondo LOIU (VIZCAYA) España
 P.O. Box 1.323/48080 Bilbao
 Tel. 34-(4) 4 71 13 00
 Fax.34-(4) 4 53 16 36

Management Systems
 Certified by
LRQA
 ISO 9001 / SGI 6000360
 ISO 14001 / SGI 1870678

ACEROS INOXIDABLES

OLARRA

OLARRA U.K. LTD.
FOREST PARK - CLEOBURY MORTIMER
NR KIDDERMINSTER - DY 14 9BD - ENGLAND

Trade Mark - Zeichen des Lieferwerkes
 Anagrama del suministrador



Works Inspector Stamp - Werkssachverständiger
 Sello del Inspector



Certificate type - APZ Nach Certificado tipo		EN 10204/3.1		Certificate n° - Prüf-Nr Certificado n°		349333		Date - Datum - Fecha 11 - 04 - 2018																							
Our order N° Werks - Nr N° de Referencia		655367		Heat Schmelze Colada		449678		Your order N° Bestell - Nr Pedido N°				OL8317																			
Steel Grade Werkstoff Calidad				316-S-11 AV				According to Entsprechend Corresponde				BS 970:PART 3:1991.																			
Shape and Size - Gegenstad Perfil y dimensión HEXAGON 22,23 mm				Tolerance - Toleranz Tolerancia h 11 /DIN 176				Bundles Bunde 4 Bultos		Bars Stäbe 259 Barras		Weight Gewicht 2678 Kg Peso																			
Requirements - Anforderungen - Exigencias												316S31AV-1.4404-1.4401-Type 316-Type 316L. PED 2014/68/EU, Annex I, Parag.4.3/DGR 2014/68/EU Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC																			
EN 10.088-3.2014. EN 10.272-2016. ASTM A 182/A 182M-16. ASTM A 479 / A 479M-17. ASTM A 276/A 276M-17. ASME SA 479 / SA 479M-15 SAE AMS 5653H-12. NACE MR-0175/ISO 15156-3 2015. NACE MR-0103/ISO 17945-2015. NORSOK M-630 and MDS S01.						Melting process / Erschmelzungsart / Proceso de Fusión E.A.F. / A.O.D.						Heat treatment / Wärmebehandlung / Tratamiento térmico 1060C 4H/Std WATER/WASSER/AGUA																			
Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estirado-																															
Test results - Ergebnis der Prüfungen - Resultados de los ensayos																															
Dimension of Specimen Abmessungen des Probestabes Medida de las probetas		Rp0.2% N/mm2 MPA		Rp 1% N/mm2 MPA		Rm N/mm2 MPA		A %L 5D		A %L 4D		Z %		Hardness Härte HBw		Impact test / Kersbschlag / Resiliencia ISO V Jules															
RD..10,00 mm.		Min. 325		375		550		20																							
Temperature °C 20		Spec. N° Probe Nr. Pro N°		1		506		582		665		38		41		73		217													
		Max.																													
		C		Si		Mn		P		S		Cr		Mo		Ni		Cu		N		Co									
Min.												16,50		2,00		11,00															
Max.		0,030		1,00		2,00		0,045		0,030		18,50		2,50		14,00		0,70													
		0,024		0,64		1,60		0,038		0,027		17,05		2,00		11,20		0,37		0,0200		0,15									
Visual and dimensional inspection Besichtigung und Ausmessung Control visual y dimensional				O.K.				Radioactivity inspection Radioaktivitätskontrolle Control de Radioactividad				O.K.				Antimixing test Spektrosk Verwechslungspr Antimezcla				O.K.				Grain Size Korngröße Tamaño de grano				5-6 ASTM E-112-13			
Remarks - Bemerkungen - Observaciones														EDV / EDP Acc. EN 10.204 Marian Tejedo Quality Mng. Works Inspector Der Werkssachverständige Inspector de fábrica																	
IC test acc./IK prüfung nach ASTM A 262 E.15. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK F13800 1/2" NPT RT HEX PLUG 10K 316L																															
We hereby certify that material described herein complies with the requirements agreed on the order.																															

Firmado digitalmente por / Signed digitally by:
 ACEROS INOXIDABLES OLARRA SA - CIF A48663546
 Fecha / Date:11-04-2018 15:23