



MUSSARI S.r.l.

Traffiana tubi inox di alta precisione
Via Repubblica 1118 - Tel 031/390677 - 031/492476
Fax 031/390010
22076 LURATE CACCIOLICOMO (ITALY)
web-site: www.mussari.com

TEST CERTIFICATE ACCORDING TO

EN 10204 / 3.1

ABNABNEPRUFZEUGNIS

CERTIFICAT D'ESSAIS

CERTIFICATO DI COLLAUDO

Comm. Int. Nr. 31/14

31/14

DELIVERY BILL - Liefererschein/Bonifico de Livraison/Bonifica di consegna

475

N. 715 - 2014

DATE - Datum/Data

20 febbraio 2014

CUSTOMER ORDER N° - Bestellung/Comanda Cliente/Ordre Client
2013251

MECHANICAL TEST

SPECIFICATIONS

ASTM A213/269 - HP Tubes - Butech Spec. 2000

TECHNOLOGICAL TEST

FLARING TEST:

FLANGE TEST:

FLATTENING TEST:

BENDING REV. TEST:

RING FLATTENING TEST:

DRIFT EXPANDING TEST:

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

YIELD POINT

TENSILE STRENGTH

ELONGATION

HARDNESS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

QUANTITY

DIMENSIONS

STEEL GRADE

Werkstoff/Innuance

Materiale

TP 316 - 316L

9/16" x 0.312"

902.55

MT

PC.

LGTH

MM

PC.

mm

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

MECHANICAL TEST

YIELD POINT

TENSILE STRENGTH

ELONGATION

HARDNESS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

STEEL GRADE

Werkstoff/Innuance

Materiale

TP 316 - 316L

9/16" x 0.312"

902.55

MT

PC.

LGTH

MM

PC.

mm

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

YIELD POINT

TENSILE STRENGTH

ELONGATION

HARDNESS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

STEEL GRADE

Werkstoff/Innuance

Materiale

TP 316 - 316L

9/16" x 0.312"

902.55

MT

PC.

LGTH

MM

PC.

mm

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

YIELD POINT

TENSILE STRENGTH

ELONGATION

HARDNESS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

REMARKS

STEEL GRADE

Werkstoff/Innuance