Larrondo LOIU (VIZCAYA) España P.O. Box 1.323/48080 Bilbao Tel. 34-(4) 4 71 13 00 Fax.34-(4) 4 53 16 36

Management Systems Cartified by LRQA ISO 9001 / SGI 6000360 ISO 14001 / SGI 1870678

## OLARRA

ACEROS INOXIDABLES

OLARRA U.K. LTD. FOREST PARK - CLEOBURY MORTIMER NRKIDDERMINSTER-DY149BD-ENGLAND

Trade Mark - Zeichen des Lieferwerkes
Anagrama del suministrador

Works Inspector Stamp - Werkssachverständiger
Sello del Inspector

			,		<u> </u>					
Certificate type - APZ Nach Certificado tipo	Certificate nº - Prūf-Nr Certificado nº 24			240240			Datum-Fech: 10 - 2015			
Our order № Werks - Nr 581688 №de Referencia	Heat Schmelze Colada	399014	Your order N Bestell - Nr Pedido Nº		.6893					
Steel Grade Werkstoff 316-S-11 AV Calidad				According Entspreche Correspond	end BS	S 97	'0:PAF	RT 3:1	991.	
Shape and Size - Gegensta Perfil y dimensión HEXAGON 41.28 mn		Tolerance Tole h 11 /[		Bundles Bunde Bultos	5	Bars Stäbe Barras	70	Weight Gewitcht Peso	2494 Kg	

Requirements - Anforderungen - Exigencias

EN 10.088-3.2014.

EN 10.272-2007.

ASTM A 182 / A 182M-15.

ASTM A 479 / A 479M-14.

ASTM A 276-15.

ASME SA 479 / SA 479M-13

NACE MR-0175-2003/ISO 15156-3 2009.

SAE AMS 5653H-12.

316S31AV-1.4404-1.4401-Type 316-Type 316L.

PED 97/23/EC, Annex I, Parag.4.3/DGR 97/23/EG

Meiting process / Erschmelzungsart / Proceso de Fusión E.A.F. / A.O.D.

Heat treatment / Wārmebehandlung / Tratamiento térmico 1060C 4H/Std WATER/WASSER/AGUA

Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC

## Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estirado-

						<del></del>									
Abmessungendes Probestabes N/m Medida de las probetas Mi		Rp0,2 N/mm MPA	12 N	Rp 1% Rr N/mm2 N/m MPA MF		m2 %L		Z %	Hardness Härte HBw	Impact test / Kersbschlag / Resiliencia ISO V Jules					
		325	325 375		5 550		0								
	,	-	Max.										entre and a firm of the section of t		A STATE OF THE STA
		Spec. Nº. Probe Nr. Pro Nº.	1	429		520	63	1 3	9 4	42	71	197			
	С	Si	М	ln .	P		3	Cr	Mo	)   	Ni	Cu	N	Со	
Min.			i				To company	16,50	2,0	0	11,00				
Max	0,030	1,00	2,0	00	0,045	0,0	0,030		2,50	)	14,00	0,70			
	0,029	0,42	1,0	52	0.035	0,0	27 *	17,25	2,0	4	11,05	0,39	0,0300	0,18	
Besic	htingung	ensionalins und Ausme y dimension	ssung		Radioa	ctivity in ktivitäts de Radio	kontro	lle O.K.	Antimi Spektri Antime	osk Ve		ngspr O.K.	Grain Size Korngröss Tamaño d	е	

Remarks - Bemerkungen - Observaciones

IC test acc./IK prüfung nach ASTM A 262 E.13. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK

TEST CERTIFICATE

VERIFIED TRUE

F11623 COPY OF ORIGINAL
1" BSPP Cone Seat x 1" NPT Male x Male Adaptor 10K

EDV / EDP Acc. EN 10.204 Alfredo Molina Certification Mng.

Works Inspector
Der Werkssachverständige
Inspector de fäbrica