


CERTIFICAT DE RECEPTION 3.2 / EN 10204:2004 Inspection Certificate 3.2 / EN 10204:2004 Abnahmeprüfzeugnis 3.2 / EN 10204:2004 Inspection Number : AEN 02846 07/019		Numéro de document Rev 00 Document number Bescheinigungsnummer 2017-117272		Page 004 Sheet / Seite 004		 ArcelorMittal
Client - Purchaser - Besteller BROWN MCFARLANE LTD - LADYWELL		Référence client - Purchase order - Kaufauftrag ST-4875/17-119				
Projet - Project - Projekt Industeel Belgium Site : Rue de Châtelet 266 6030 Marchienne-au-Pont				ISO 9001 (Cert ES081397, Valid 14/09/2018) + MAQ REV 12 du 02/05/2012 ISO 9001 (Cert ES081397, Valid 14/09/2018) + QAM REV 12 of 02/05/2012		
Produit - Product - Erzeugnis Plate(s)		Commande / Poste - Internal order - Werksbestellung 1071181 / 000140				
Bordereau de livraison - Delivery note - Lieferungsdokument						80313267


#082-ESSAIS/TECHNOLOGIQUES/TECHNOLOGICAL TESTS/TECHNOLOGISCHE PRÜFUNGEN

CORROSION - CORROSION - KORROSION							Sensibilisé - Sensitized - Sensibilisiert															
EN ISO 3651-2 A																						
Test description - Prüfbeschreibung																						
N° lot QM	Etat	Loc	Epr.	T°	Uni	Mac																
840036.5001	001	T3/4	SSS	20	°C																	
Test result							Satisfactory as per specification															

CORROSION - CORROSION - KORROSION							Sensibilisé - Sensitized - Sensibilisiert															
ASTM A262 E																						
ASTM A262 E - ASTM A262 E																						
N° lot QM	Etat	Loc	Epr.	T°	Uni	Mac																
840036.5001	002	T3/4	SSS	20	°C																	
Test result							Satisfactory as per specification															


Loc	3/4	Trois-Quart - 3/4 Width - 3/4 Breite	
Loc	T	Tête - Top - Kopf	
Epr. Epaisseur	S	Standard - Standard - Standard	
Epr. Face	S	Supérieure - Upper face - obere	
Epr. Sens	S	Standard - Standard - Standard	
Etat	001	SENSI - Sensitization (From 350 °C at 220 °C/h to 700 °C (-10/+10) (min: 30 min) - Down to 350 °C at 220 °C/h - 1 Cycle) - SENSI	
Etat	002	SENSI - Sensitization (From 350 °C at 220 °C/h to 675 °C (-25/+0) (min: 60 min) - Down to 350 °C at 220 °C/h - 1 Cycle) - SENSI	
Epr. Ep./Face/Sens	SSS	Standard - Standard - Standard / Supérieure - Upper face - obere / Standard - Standard - Standard	

CERTIFIED THAT THIS IS A TRUE COPY OF ORIGINAL CERTIFICATE RETAINED IN OUR FILE

Signed 
 FOR - BROWN MCFARLANE LTD
 G. PARKES

Nous certifions que les produits ci-dessus sont conformes aux prescriptions de la commande.
 We hereby certify that the above mentioned products are complying with the order requirements.
 Wir bestätigen hiermit, dass die obengenannten Erzeugnisse den Bestimmungsvorschriften entsprechen.

Lloyd's Register EMEA Energy
 Antwerp Office
 M. Matijasevic-Clarke



STÉPHANIE WALLEMACQ
 06/07/2017
 Gestionnaire Commande
 Mill Inspector
 Werksbeauftragte

