

Larrondo LOIU (VIZCAYA) España  
 P.O. Box 1.323/48080 Bilbao  
 Tel. 34-(4) 4 71 13 00  
 Fax.34-(4) 4 53 16 36

Management Systems  
 Certified by  
**LRQA**  
 ISO 9001 / SGI 6000360  
 ISO 14001 / SGI 1870678

ACEROS INOXIDABLES

**OLARRA**

Trade Mark - Zeichen des Lieferwerkes  
 Anagrama del suministrador



Works Inspector Stamp - Werkssachverständiger  
 Sello del Inspector



Certificate type - APZ Nach Certificado tipo		EN 10204/3.1		Certificate n° - Prüf-Nr Certificado n°		199077		Date - Datum - Fecha 03 - 07 - 2014			
Our order N° Werks - Nr N° de Referencia		546912		Heat Schmelze Colada		264085		Your order N° Bestell - Nr Pedido N°			
								OL6332			
Steel Grade Werkstoff Calidad				X-2-CRNIMO-17-12-2 / 1.4404 MECAMAX				According to Entsprechend Corresponde		EN 10.272-2007.	
Shape and Size - Gegenstad Perfil y dimensión HEXAGON 14,29 mm			Tolerance - Toleranz Tolerancia h11 /DIN 176 /EN 10278			Bundles Bunde Bultos	3	Bars Stäbe Barras	Weight Gewicht Peso		1271 Kg
Requirements - Anforderungen - Exigencias											
EN 10.088-3.2005. ASTM A 479 / A 479M-13b. ASTM A 276-13a. ASME SA 479 / SA 479M-13 SAE AMS 5653H-12. NACE MR-0175-2003/ISO 15156-3 2009. 1.4401-Type 316-Type 316L. PED 97/23/EC, Annex I, Parag.4.3/DGR 97/23/EG Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC											
Melting process / Erschmelzungsart / Proceso de Fusión					Heat treatment / Wärmebehandlung / Tratamiento térmico						
E.A.F. / A.O.D.					1060C 4H/Std WATER/WASSER/AGUA						
Solution annealed/Abgeschreckt/Hiptemple-Cold drawn/Gezogen/Estirado-											
Test results - Ergebnis der Prüfungen - Resultados de los ensayos											
Dimension of Specimen Abmessungen des Probestabes Medida de las probetas		Rp0.2% N/mm2 MPA	Rp 1% N/mm2 MPA	Rm N/mm2 MPA	A %L 5D	A %L 4D	Z %	Hardness Härte HBw	Impact test / Kerschlag / Resiliencia ISO V Jules		
RD. 10,00 mm.		Min.	200	235	500	20					
		Max.			900			315			
Temperature °C 20	Spec. N° Probe Nr. Pro N°	1	550	630	693	41		67	212		
	C	Si	Mn	P	S	Cr	Mo	Ni	N	Co	
Min.						16,50	2,00	10,00			
Max.	0,030	1,00	2,00	0,045	0,030	18,50	2,50	13,00	0,1000		
	0,016	0,588	1,53	0,029	0,027	16,64	2,03	10,07	0,0480	0,387	
Visual and dimensional inspection Besichtigung und Ausmessung Control visual y dimensional			Radioactivity inspection Radioaktivitätskontrolle Control de Radioactividad			Antimixing test Spektroskop Verwechslungspr Antimezcla			Grain Size Korngröße Tamaño de grano		
O.K.			O.K.			O.K.					
Remarks - Bemerkungen - Observaciones											
IC test acc./IK prüfung nach ASTM A 262 E.02. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK						<b>FLOW TECHNOLOGY LTD</b> <b>TEST CERTIFICATE</b> <b>VERIFIED TRUE</b> <b>COPY OF ORIGINAL</b>			EDV / EDP Acc. EN 10.204 Alfredo Molina Certification Mng.		
F9432 7/16" JIC Swivel x Swivel Adaptor 10K									Works Inspector Der Werkssachverständige Inspector de fábrica		