

Larrondo LOIU (VIZCAYA) España
P.O. Box 1.323/48080 Bilbao
Tel. 34-(4) 4 71 13 00
Fax 34-(4) 4 53 16 36

Management Systems
Certified by
LRQA
ISO 9001 / SGI 6000366
ISO 14001 / SGI 1870678

ACEROS INOXIDABLES

OLARRA

OLARRA U.K. LTD.
FOREST PARK - CLEOBURY MORTIMER
NR KIDDERMINSTER - DY 14 9BD - ENGLAND

Trade Mark - Zeichen des Lieferwerkes
Anagrama del suministrador



Works Inspector Stamp - Werkssachverständiger
Sello del Inspector



Certificate type - APZ Nach Certificado tipo		EN 10204/3.1		Certificate nº - Prüf-Nr Certificado nº		195828		Date - Datum - Fecha		09 - 06 - 2014													
Our order Nº Werks - Nr Nº de Referencia		543318		Heat Schmelze Colada		373076		Your order Nº Bestell - Nr Pedido Nº		OL6292													
Steel Grade Werkstoff Calidad				316-S-11 AV				According to Entsprechend Corresponde				BS 970:PART 3:1991.											
Shape and Size - Gegenstand Perfil y dimensión				Tolerance - Toleranz Tolerancia				Bundles Bunde		4		Bars Stäbe		323		Weight Gewicht		2460 Kg					
HEXAGON 19,05 mm				h 11 / DIN 176				Bultos				Barras				Peso							
Requirements - Anforderungen - Exigencias												Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC											
EN 10.088-3.2005. EN 10.272-2007. ASTM A 182 / A 182M-13a. ASTM A 479 / A 479M-13b. ASTM A 276-13a. ASME SA 479 / SA 479M-13 SAE AMS 5653H-12. NACE MR-0175-2003/ISO 15156-3 2009. 316S31AV-1.4404-1.4401-Type 316-Type 316L. PED 97/23/EC, Annex I, Paraq.4.3/DGR 97/23/EG																							
Melting process / Erschmelzungsart / Proceso de Fusión						Heat treatment / Wärmebehandlung / Tratamiento térmico																	
E.A.F. / A.O.D.						1060C 4H/Std WATER/WASSER/AGUA																	
Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estirado-																							
Test results - Ergebnis der Prüfungen - Resultados de los ensayos																							
Dimension of Specimen Abmessungen des Probestabes Medida de las probetas		Rp0,2% N/mm2 MPA		Rp 1% N/mm2 MPA		Rm N/mm2 MPA		A %L 5D		A %L 4D		Z %		Hardness Härte HBw		Impact test / Kerschlag / Resiliencia ISO V Jules							
RD. 10,00 mm.		Min.		325		375		550		20													
		Max.																					
Temperature °C 20		Spec. Nº. Probe Nr. Pro Nº.		1		437		543		630		38		41		74		207					
		C		Si		Mn		P		S		Cr		Mo		Ni		Cu		N		Co	
Min.												16,50		2,00		11,00							
Max.		0,030		1,00		2,00		0,045		0,030		18,50		2,50		14,00		0,70					
		0,023		0,48		1,71		0,035		0,029		17,10		2,03		11,00		0,40		0,0280		0,17	
Visual and dimensional inspection Besichtigung und Ausmessung Control visual y dimensional				Radioactivity inspection Radioaktivitätskontrolle Control de Radioactividad				Antimixing test Spektrosk Verwechslungspr Antimezcla				Grain Size Korngröße Tamaño de grano											
O.K.				O.K.				O.K.															
Remarks - Bemerkungen - Observaciones																							
IC test acc./IK prüfung nach ASTM A 262 E.02. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK																							
<div style="border: 1px solid red; padding: 5px; display: inline-block;"> FLOW TECHNOLOGY LTD TEST CERTIFICATE VERIFIED TRUE COPY OF ORIGINAL </div>																							
F9516 3/8" MP x 9/16" JIC Male x Male Adaptor 15K																							
EDV / EDP Acc. EN 10.204 Alfredo Molina Certification Mng. Works Inspector Der Werkssachverständige Inspector de fábrica																							