

Larrondo LOIU (VIZCAYA) España
P.O. Box 1.323/48080 Bilbao
Tel. 34-(4) 4 71 13 00
Fax.34-(4) 4 53 16 3

Management Systems
Certified by
LRQA
ISO 9001 / SGI 6000360
ISO 14001 / SGI 1870678

ACEROS INOXIDABLES

OLARRA

OLARRA U.K. LTD.
FOREST PARK - CLEOBURY MORTIMER
NR KIDDERMINSTER - DY 14 9BD - ENGLAND

Trade Mark - Zeichen des Lieferwerkes
Anagrama del suministrador



Works Inspector Stamp - Werkssachverständiger
Sello del Inspector



| | | | | | | | | | | | |
|--|---------------------------------|------------------------|---|--|------------|--|--------|---|--|---------------------------|------|
| Certificate type - APZ Nach Certificado tipo | | EN 10204/3.1 | | Certificate n° - Prüf-Nr Certificado n° | | 201823 | | Date - Datum - Fecha 24 - 07 - 2014 | | | |
| Our order N° Werks - Nr N° de Referencia | | 546853 | | Heat Schmelze Colada | | 374439 | | Your order N° Bestell - Nr Pedido N° | | | |
| | | | | | | | | OL6326 | | | |
| Steel Grade Werkstoff Calidad | | | | 316-S-11 AV | | | | According to Entsprechend Corresponde | | | |
| | | | | | | | | BS 970:PART 3:1991. | | | |
| Shape and Size - Gegenstand Perfil y dimensión | | | Tolerance - Toleranz Tolerancia | | | Bundles Bunde Bultos | | Bars Stäbe Barras | | Weight Gewicht Peso | |
| HEXAGON 22,23 mm | | | h 11 /DIN 176 | | | 4 | | 231 | | 2375 Kg | |
| Requirements - Anforderungen - Exigencias | | | | | | | | | | | |
| EN 10.088-3.2005. EN 10.272-2007. ASTM A 182 / A 182M-13a. ASTM A 479 / A 479M-13b. ASTM A 276-13a. ASME SA 479 / SA 479M-13 SAE AMS 5653H-12. NACE MR-0175-2003/ISO 15156-3 2009. 316S31AV-1.4404-1.4401-Type 316-Type 316L. PED 97/23/EC, Annex I, Paraq.4.3/DGR 97/23/EG | | | | | | Anhang I Absatz 4.3 Certificate/Zertifikat Nr. 348/2008/MUC | | | | | |
| Melting process / Er schmelzungsart / Proceso de Fusión | | | | | | Heat treatment / Wärmebehandlung / Tratamiento térmico | | | | | |
| E.A.F. / A.O.D. | | | | | | 1060C 4H/Std WATER/WASSER/AGUA | | | | | |
| Solution annealed/Abgeschreckt/Hipertemple-Cold drawn/Gezogen/Estirado- | | | | | | | | | | | |
| Test results - Ergebnis der Prüfungen - Resultados de los ensayos | | | | | | | | | | | |
| Dimension of Specimen Abmessungen des Probestabes Medida de las probetas | | Rp0.2% N/mm2 MPA | Rp 1% N/mm2 MPA | Rm N/mm2 MPA | A %L 5D | A %L 4D | Z % | Hardness Härte HBw | Impact test / Kersbschlag / Resiliencia ISO V Jules | | |
| RD. 10,00 mm. | | Min. | 325 | 375 | 550 | 20 | | | | | |
| | | Max. | | | | | | | | | |
| Temperature °C 20 | Spec. N° Probe Nr. Pro N° | 1 | 451 | 561 | 637 | 36 | 39 | 73 | 212 | | |
| | | | | | | | | | | | |
| | C | Si | Mn | P | S | Cr | Mo | Ni | Cu | N | Co |
| Min. | | | | | | 16,50 | 2,00 | 11,00 | | | |
| Max. | 0,030 | 1,00 | 2,00 | 0,045 | 0,030 | 18,50 | 2,50 | 14,00 | 0,70 | | |
| | 0,022 | 0,36 | 1,79 | 0,036 | 0,028 | 16,95 | 2,01 | 11,05 | 0,37 | 0,0230 | 0,15 |
| Visual and dimensional inspection Besichtigung und Ausmessung Control visual y dimensional | | | Radioactivity inspection Radioaktivitätskontrolle Control de Radioactividad | | | Antimixing test Spektrsk Verwechslungspr Antimezcla | | | Grain Size Korngröße Tamaño de grano | | |
| O.K. | | | O.K. | | | O.K. | | | | | |
| Remarks - Bemerkungen - Observaciones | | | | | | | | | | | |
| IC test acc./IK prüfung nach ASTM A 262 E.02. OK Crack control/Rissgeprüft acc. EN 10277-1 class 2. OK | | | | | | FLOW TECHNOLOGY LTD TEST CERTIFICATE VERIFIED TRUE COPY OF ORIGINAL | | | EDV / EDP Acc. EN 10.204 Alfredo Molina Certification Mng. | | |
| F9727 3/8"NPT X 3/4" JIC M/M ADAPTOR 10K 316L | | | | | | | | | Works Inspector Der Werkssachverständige Inspector de fábrica | | |